

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H04Q 3/00	A1	(11) International Publication Number: WO 99/23839 (43) International Publication Date: 14 May 1999 (14.05.99)
(21) International Application Number: PCT/US98/22944 (22) International Filing Date: 29 October 1998 (29.10.98) (30) Priority Data: 08/962,478 31 October 1997 (31.10.97) US (71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US). (72) Inventor: PATEL, Mahesh; 6529 Roundrock Trail, Plano, TX 75023 (US). (74) Agents: MOORE, Stanley, R. et al.; Jenkins & Gilchrist, P.C., Suite 3200, 1445 Ross Avenue, Dallas, TX 75202 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: METHOD TO SUPPRESS NUMBER PORTABILITY DATABASE QUERIES**(57) Abstract**

A system and method for suppressing redundant database queries between two switching points in a telecommunications system, where the switching points are unable to utilize the ISUP communication protocol. The system and method are implemented by using a parameter of the communications protocol to indicate whether a database query has been performed. When the receiving switch receives the information, the switch is suppressed from performing a redundant database query by the parameter of the communications protocol.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

METHOD TO SUPPRESS NUMBER PORTABILITY DATABASE QUERIES

BACKGROUND OF THE PRESENT INVENTION

5 Field of the Invention

The present invention relates to telecommunications systems and methods for routing calls, and specifically to providing a technique for routing calls in a number portability environment.

10

Background and Objects of the Present Invention

Ordinarily, subscriber directory numbers are geographic in that the subscriber number relates to a certain geographic area within the domain of the numbering plan. For example, in North America, the first six digits of the subscriber directory or phone number identifies the particular switch that serves the subscriber. The last four digits identify the particular subscriber connected to the switch.

20 A telecommunications network uses the information in the first six digits of the phone number to route and to terminate the call. This manner of routing calls requires that the directory numbers be tied to the serving switch, as opposed to a subscriber. A subscriber who changes switches must change their directory number. If the actual directory numbers were not changed, a call to the subscriber would be routed to the wrong switch.

25 The requirement that the directory number be tied to the serving switch is problematic for several reasons. Persons who have to change numbers because of relocation experience a certain degree of inconvenience brought on by having to notify others of their new directory number. This requirement also presents a major hurdle for wireless mobile systems, where unlike in a conventional wire line system, a mobile system subscriber does not belong to any

30

35

-2-

one switch. Instead, the mobile subscriber is served by a local switch in the area that the subscriber is currently roaming. Accordingly, a call terminating to a mobile subscriber cannot be terminated using the directory number alone.

5 A common method, used to route a call terminating at a mobile subscriber, is to route the call to a switch operated by the mobile subscriber's service provider (the gateway switch). The gateway switch then refers to a home location register (HLR) to locate the mobile subscriber. 10 When the mobile subscriber is located, the gateway switch determines the particular switch which serves the area within which the subscriber is roaming, obtains a temporary number from a pool of numbers at that switch, 15 and uses the temporary number to terminate the call. This method is advantageous because it does not require changes or modifications in the routing tables of intermediate switches.

20 If a mobile subscriber changes service providers, however, the above method fails and the mobile subscriber will still have to change their directory number. The reason for the failure is that the directory number is used to route the call to the gateway switch, and a call routed on the called subscriber number will terminate at 25 the wrong switch.

A solution that has been proposed is enable the intermediate switch that routes the call to recognize the directory number as a portable number. A portable number is the first six digits of any subscriber number that has 30 ported. As is understood in the art, when the switch recognizes the number as portable, a query is launched to a database to obtain routing information. If the called number is ported (no longer served by the original switch), then a Location Routing Number (LRN) is returned 35 which is used to route the call further.

After routing the call, the receiving switch would normally also recognize the number as portable and again

-3-

launch a database query. This problem may be solved by having the sending switch insert the information obtained from the database into the packet of information that is routed. When a switch routes a call, it builds and transmits a packet of information pertaining to the call to the receiving switch. One way to format this information is according to the Integrated Services Digital Network User Part (ISUP) protocol.

When a switch prepares a packet of information to send, it builds the packet pursuant to ISUP protocol. By the setting of certain ISUP parameters the subsequent switch, upon the receipt of the information packets, may determine that the aforementioned database query has been performed, that the called number is the LRN and that the real called number resides in some other ISUP parameter. Accordingly, redundant database queries are avoided.

However, not all switches are capable of communication according to the ISUP protocol. For example, a number of switches utilize a protocol known as multi-frequency (MF). The MF protocol employs different parameters for indicating the results of a database query as in ISUP. Thus, when end-to-end ISUP is not available, multiple database queries are likely to occur resulting in longer call setup times and excessive use of network resources.

It is therefore an object of the present invention to suppress multiple database queries when a call is routed between switches that do not have end-to-end ISUP.

SUMMARY OF THE INVENTION

The present invention is directed to a method for routing communications between two switches in a telecommunications system with portable numbers which are not capable of utilizing the ISUP protocol by having the second switch determine if the directory number is portable, examining a database query flag within the non-ISUP protocol, and if the flag is set, suppressing a

-4-

database query, and if not set, performing a database query and setting the flag to further suppress further database queries. The present invention is also directed to a system for routing a communication in a telecommunications system by using two switches, a communications protocol for communications between the two switches, a portable number detector for recognizing a call terminating at a portable number a query status determiner for determining whether a database query has been performed and performing a database query when one has not been performed, and an indicator which is set once the database query has been performed. The invention is also directed to an apparatus for routing telephone calls in a telecommunications network including an incoming line, an outgoing line, a portable number detector for recognizing a call terminating at a portable number, a query status determiner for determining whether a database query has been performed and performing a database query when a database query has not been performed, an indicator for indicating that a database query has been performed and a transmitter for transmitting the indicator on the outgoing line.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed inventions will be described with reference to the accompanying drawings, which illustrate sample embodiments of the invention and which are incorporated in the specification hereof by reference, wherein:

FIGURE 1 is a diagram illustrating Service Switching Points serving a local exchange in a telephone network;

FIGURE 2a is a block diagram illustrating a switch with an incoming Integrated Services Digital Network User Part (ISUP) line and an outgoing Multi-Frequency (MF) line;

FIGURE 2b is a block diagram illustrating a switch with an incoming MF line and an outgoing ISUP line;

-5-

FIGURE 2c is a block diagram illustrating a switch with an incoming MF line and an outgoing MF line;

FIGURE 3 is a flow diagram illustrating the operation of a switch with an incoming ISUP line and an out-going MF line;

FIGURE 4 is a flow diagram illustrating the operation of a switch receiving a call on a MF line and sending a call on an ISUP line; and

FIGURE 5 is a flow diagram illustrating the operation of a switch receiving a call on a MF line and sending a call on a MF line.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EXEMPLARY EMBODIMENTS

The numerous innovative teachings of the present application will be described with particular reference to the presently preferred exemplary embodiments. However, it should be understood that these embodiments provide only a few examples of the many advantageous uses of the innovative teachings herein. It should be understood that statements made in the specification of the present application do not necessarily delimit any of the various claimed inventions. Moreover, some statements may apply to some inventive features but not to others.

Referring now to FIGURE 1 of the drawings, several Service Switching Points (SSPs) 100 are illustrated, each serving as local exchanges in a telephone network 190. The SSPs 100 also provide an Integrated Services Digital Network (ISDN) User Part (ISUP) protocol for Signal Transfer Points (STPs) 110, as is understood in the art.

Each STP 110 serves as a router, and switches messages received from a particular SSP 100 through the network 190 to their appropriate destinations (another SSP 100). It should be understood that the STPs 110 preferably receive such messages in packet form from the SSPs 100. These packets are either related to call

-6-

connections or database queries. If the packet is a request to connect a call, the message is forwarded to a destination end office (another SSP 100), where the call will be terminated.

5 If, however, the message is a database query seeking additional information, the destination will, of course, be a database, such as database 115. Access to the database 115 is provided through a Service Control Point (SCP) 120, which is attached to the network 190 through
10 a respective STP 110. In particular, the SCP 120 acts as an interface to a computer (not shown) that houses the requested information in the database 115.

Presently, a subscriber attached to one SSP 100 has the ability to move to a different SSP 100 and retain
15 their public directory number. This feature is referred to as number portability. An obvious advantage of number portability is that other subscribers can connect to the portable subscriber without memorizing another phone number or otherwise changing to their dialing procedures.

20 If, however, a subscriber has been ported-out to another SSP 100, an Initial Address Message (IAM) sent by the originating SSP 100 must be modified to account for the change in the terminating SSP. Local Number Portability (LNP) refers to a database that holds a
25 Location Routing Number (LRN), which is a ten-digit number used to uniquely identify the switch that has the ported-out number. Specifically, the LRN is the number for the recipient switch, which is the switch that has ported-in a number from another switch (called a donor switch).
30 This ported-in number was not previously served by the recipient switch.

Typically, a SSP 100 sends an LNP query to the SCP 120, which accesses the LNP database in order to retrieve the routing information for a ported subscriber. The
35 query response by the SCP 120 provides that SSP 100 with both the pertinent LRN, which is populated (that is placed) in a Called Party Number (CPN) parameter in the

-7-

IAM, and a Ported Dialed Number (PDN), e.g., the actual dialed digits for the ported-out subscriber, which is placed in the Generic Address Parameter (GAP) in the IAM. A Forward Call Indicator (FCI) (M-bit) in the IAM is then
5 updated to indicate that the number has been translated. The FCI M-bit is used as a fail-safe mechanism to prevent more than one LNP query from being launched on a call. However, if a given SSP 100 or STP 110 does not use the ISUP protocol, it will not be possible to update the M-bit
10 or include the LRN.

Referring now to Figure 2a, a block diagram illustrating a switch 210 with an incoming ISUP line 260 and outgoing MF line 230 is described. The switch 210 may be, but is not limited to, an SSP 100 or an STP 110, and
15 includes an applications module (APPL) 220 which builds a communications protocol when the switch is sending or receiving a signal. Messages in this embodiment are received by the switch 210 via the ISUP line 260 and are sent via the MF line 230 (such as Multi-Frequency).

Referring now to Figure 2b, a block diagram illustrating a switch 212 with an incoming MF line 262 and an outgoing ISUP line 232 is described. The switch 212 may be, but is not limited to, an SSP 100 or an STP 110 and comprises an applications module (APPL) 222 which
25 builds a communications protocol when the switch is sending or receiving a signal. Messages in this second switch embodiment are received by the switch via the MF line 262 and are sent via the ISUP line 232.

Referring now to Figure 2c, a block diagram illustrating a switch 214 with an incoming MF line 264 and an outgoing MF line is described 234. The switch 214 may be, but is not limited to, an SSP 100 or an STP 110 and
30 comprises an applications module (APPL) 224 which builds a communications protocol when the switch is sending or receiving a signal. Messages in this third switch embodiment are received by the switch via the MF line 264 and are sent via the MF line 234.
35

-8-

Although the switches 210, 212, and 214 are shown with only one incoming line, 260, 262, 264, and only one outgoing line 230, 232, 234, those skilled in the art will understand that telecommunications switches (such as 100, 210, 212, or 214) have a plurality of incoming (such as 260, 262, or 264) and outgoing lines (such as 230, 232, or 264) connecting to other switches (such as 100, 210, 212, or 214) in a network. The communications protocol for the incoming (such as 260, 262, or 264) and outgoing lines (such as 230, 232, or 264) will depend on the communications protocols of the switches (such as 100, 210, 212, or 214) that the line (such as 260, 262, 264, 230, 232, or 264) connects.

Those skilled in the art will also recognize a number of ways that a switch (such as 100, 210, 212, or 214) can select which communications protocol to use. For example, this can be determined by maintaining in memory, a table identifying which protocol to utilize when communicating with another switch. Another method would be to place the table in a database (such as 115). Another way to select the communications protocol would be to send an initial request to the receiving switch (such as 100, 210, 212, or 214) and examining the reply. Yet another way would be for the switch (such as 100, 210, 212, or 214) to recognize the physical characteristics of the line (such as 260, 262, 264, 230, 232, or 264) itself and determine the communications protocol.

Referring now to Figure 3 there is shown a flow diagram illustrating the operation of the switch 210, shown in Figure 2a, with the incoming ISUP line 260 and the outgoing MF line 230 after receiving a call. In step 301, the switch 210 first determines whether the directory number dialed is a portable number. If the number is not portable, the switch proceeds to route the call along MF line 230 (step 308). On the other hand, if in step 301 the directory number is portable, the switch 210 then checks the ISUP parameters (step 302) and determines (step

-9-

303) if a previous switch has performed a database query. If the ISUP parameters indicate that a database query was not performed, the switch will initiate such a query to the SCP 120 and obtain an LRN (step 304). If however, the parameters indicate that a database query was already performed, the switch 210 will then further examine the ISUP parameters (step 305).

In either case, the switch 210 determines whether the called directory number was ported or not (step 306). If the called directory number is not ported, the switch 210 preferably directs the APPL 220 to insert a database query suppression code in the ISUP protocol. However, since the outgoing line 230 in this embodiment is MF, this cannot be done. Instead, the switch 210 directs the APPL 220 to set an Automatic Number Identification (ANI) value, a parameter within the MF protocol, to indicate that further database inquiries need not be performed (step 307) before routing the call on the MF line 230 (step 308).

In the case where the called directory number is ported, the called directory number cannot be used for routing. Because the MF line 230 cannot be enabled to transmit the LRN, the receiving switch will therefore have to launch a database query to further route the call. Accordingly, in this instance a database query should not be suppressed and the ANI value is not set.

Referring now to Figure 4, a flow diagram illustrating the operation of the switch 212, shown in Figure 2b, receiving a call on the MF line 262 and sending the call on the ISUP line 232. After receiving the call across the MF line 262, the switch 212 determines, based on the called directory number, whether the directory number is portable (step 401). If not, the switch 212 proceeds to send the call along the ISUP line 232 (step 410). If, however, the called directory number is portable, the switch 212 then examines the ANI value (step 402), and, based on the ANI value, determines whether a database query should be performed (step 403).

-10-

5 If the ANI value is set (step 403), i.e., further database inquiries are unnecessary, then the switch 212 directs the application module 222 to insert a suppression code into the ISUP protocol built by the application module 222 (step 407), and the call is then transmitted on the ISUP line 232 (step 408).

10 If the ANI value is not set (step 403), then the switch 212 initiates a query to the SCP 120 and obtains an LRN (step 404). From the query, the switch 212 is able to determine whether the called directory number is ported (step 405). If the called directory number is so ported, then the switch 212 directs the application module 222 to insert the LRN into the ISUP protocol built by the application module 222 (step 406). If, however, the
15 called number is not ported, this insertion step is bypassed. In either case, the switch 212 directs the application module 222 to insert a suppression code into the ISUP protocol built by the application module 222 (step 407), and the call is then transmitted on the ISUP
20 line 232 (step 408).

With reference now to Figure 5, a flow diagram illustrating the operation of a switch 214, shown in Figure 2c, receiving a call on the MF line 264 and sending the call on the MF line 234 is described. After
25 receiving the call across the MF line 264, the switch 214 determines, based on the called directory number, whether the directory number is portable (step 501). If not, the switch 214 proceeds to send the call along the MF line 234 (step 510). If the called directory number is portable,
30 the switch 214 examines the ANI value (step 502), and based on the ANI value, determines whether a database query should be performed (step 503).

As discussed in connection with the other switch embodiments, if the ANI value is set, then the call is
35 transmitted by the non-ISUP line 234 (step 508). If, however, the ANI value is not set, then the switch 214 initiates a query to the SCP 120 and obtains an LRN (step

-11-

504). From the query, the switch 214 is able to determine whether the called directory number is ported (step 505). If the called directory number is ported, then the call is transmitted by the MF line 234 (step 508). If the
5 called directory number is not ported, the switch 214 directs the application module 224 to set the ANI value (step 507), and the call is transmitted by the MF line 234 (step 508).

10 Although the invention has been described with a certain degree of particularity, it should be recognized that elements thereof may be altered by persons skilled in the art without departing from the spirit and scope of the invention. For example, the communications protocol is not limited to MF alone. Likewise, the parameter value
15 which indicates whether to suppress subsequent database queries need not be limited to the ANI value. Therefore, the invention is limited only by the following claims and their equivalents.

-12-

WHAT IS CLAIMED IS:

1. A method for routing a communication from a first switch to a second switch in a telecommunications system, said telecommunications system employing number portability and a communications protocol, said method
5 comprising the steps of:
determining, at said second switch, if a directory number associated with said communication from said first switch is a portable number, said communication being
10 routed through said second switch if said directory number is not portable; and
examining, by said second switch, a database query flag within said first communications protocol, said communications protocol is a non-Integrated Services
15 Digital Network User Part protocol, where if said flag is set, a number portability database query for said communication was performed at said first switch, otherwise initiating, at said second switch, a number portability database query.
20
2. The method of claim 1, further comprising the step of: setting, after initiation of said number portability database query at said second switch, said
25 database query flag.
3. The method of claim 1, wherein said communications protocol is a multi-frequency protocol.
30
4. The method of claim 3, wherein said database query flag comprises a parameter of the multi-frequency protocol.
- 35 5. The method of claim 4, wherein said parameter of the multi-frequency protocol is an automatic number identification.

-13-

6. A system for routing communications in a telecommunications system comprising:

a first switch;

5 a second switch operably coupled to said first switch;

a communications protocol for communicating between said first switch and said second switch, said communications protocol being a non-Integrated Digital Services Network User Part protocol;

10 a portable number detector for recognizing if a communication terminates at a portable number;

query status determining means for determining whether a number portability database query has been performed by said first switch and for performing said number portability database query if said query has not been performed by said first switch; and

15 an indicator, said indicator being set if said first switch performs said number portability database query.

20 7. The system of claim 6, wherein said indicator comprises a parameter of communications protocol.

8. The system of claim 6, wherein said communications protocol is a multi-frequency protocol.

25 9. The system of claim 8, wherein said indicator comprises a parameter of the multi-frequency protocol.

30 10. The system of claim 9, wherein said parameter of the multi-frequency protocol comprises an automatic number identification.

11. A switch for routing communications in a telecommunications network comprising:

35 an incoming line for receiving a given communication;
an outgoing line for sending said given communication;

-14-

a portable number detector for recognizing if said given communication terminates at a portable number;

query status determining means for determining whether a number portability database query has been performed by another switch and for performing number portability database query if said query has not been performed by said another switch;

an indicator, said indicator being set if said switch performs said number portability database query; and

a transmitter for transmitting said indicator on said outgoing line.

12. The switch of claim 11, wherein said incoming line utilizes a multi-frequency communications protocol.

13. The switch of claim 11, wherein said outgoing line utilizes a multi-frequency communications protocol.

14. The switch of claim 13, wherein said indicator further comprises setting a parameter of the multi-frequency protocol when a database query has been performed.

15. The switch of claim 14, wherein said parameter of the multi-frequency protocol is an automatic number identification.

16. The switch of claim 11 wherein said incoming line is connected to a second switch, said given communication being routed from said second switch to said switch via said incoming line.


17. The switch of claim 11 wherein said indicator being being set where query status determining means determines that said number portability database query has been performed.

-15-




18. The switch of claim 17 wherein said incoming line utilizes a multi-frequency communications protocol.

5 19. The switch of claim 17 wherein said outgoing line utilizes a multi-frequency communications protocol.

10 20. The switch of claim 19, wherein said indicator further comprises setting a parameter of the multi-frequency protocol when a database query has been performed.

**FIG. 1**

2/5

*FIG. 2A**FIG. 2B**FIG. 2C*

3/5




FIG. 3

4/5




FIG. 4

5/5




FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 98/22944

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H0403/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 751 691 A (SIEMENS STROMBERG CARLSON) 2 January 1997 see page 2, line 39 - page 3, line 9 see page 4, line 3 - line 13 see page 6, line 21 - line 40; figure 2 see page 7, line 31 - page 8, line 14; figures 3-6 see page 9, line 3 - line 21; figure 7 ---	1-4, 6-9, 11-14, 16-20
A	US 5 664 005 A (EMERY M J ET AL) 2 September 1997 see page 20, line 20 - line 65 --- -/--	1-15

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

26 March 1999

Date of mailing of the international search report

08/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vercauteren, S

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/22944

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 661 792 A (AKINPELU A A ET AL) 26 August 1997 see column 1, line 1 - column 2, line 47 see column 6, line 25 - line 32 see column 7, line 26 - column 9, line 32 ---	1-20
A	GB 2 305 815 A (NORTHERN TELECOM LTD) 16 April 1997 see page 7, line 14 - page 8, line 10 -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/22944

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0751691	A	02-01-1997	US 5748724 A	05-05-1998
			US 5689555 A	18-11-1997
			CA 2180228 A	31-12-1998
			US 5696816 A	09-12-1997
			US 5771284 A	23-06-1998
			US 5796813 A	18-08-1998
			US 5883950 A	16-03-1999
US 5664005	A	02-09-1997	US 5469496 A	21-11-1995
			US 5353331 A	04-10-1994
			US 5579379 A	26-11-1996
			US 5506887 A	09-04-1996
			US 5610972 A	11-03-1997
			US 5758281 A	26-05-1998
			WO 9318606 A	16-09-1995
US 5661792	A	26-08-1997	CA 2156002 A	19-04-1996
			CA 2232772 A	19-04-1996
			EP 0708570 A	24-04-1996
			JP 8214059 A	20-08-1996
GB 2305815	A	16-04-1997	US 5793857 A	11-08-1998
			AU 694055 B	09-07-1998
			AU 6574696 A	10-04-1997
			CA 2185376 A	28-03-1997

THIS PAGE BLANK (uspto)